

EDGE

E88

E88 is produced in two versions: E88 electric 24V model, E88 DK diesel Kubota model. E88 range is reliable and practical, suitable from medium to wide surfaces.



	E88	E88 DK
CODE	5133	5134
RUNS ON	24V Battery 3.390W	Kubota diesel motor/ 2 cyl. water cooled
MAX SPEED FORWARD	2.20 m/sec	2.20 m/sec
CENTRAL BRUSH WIDTH Ø 350	900mm	900mm
CENTRAL BRUSH WIDTH + 1 BRUSH RH	1150mm	150mm
CENTRAL BRUSH WIDTH + 2 SIDE BRUSHES	1440mm	1440mm
MAX. CLEANING CAPACITY (WITH 2 SIDE BRUSHES)	11500 m ² /h	11500 m ² /h
MAX GRADIENTS IT CAN WORK ON	20%	20%
TRACTION	Electronic on rear wheels	Hydraulic
TRANSMISSION	Electric (3.20kW)	Diesel motor (12.75kW)
WHEELS	Anti-trace wheels	Standard black wheels
CONTAINER CAPACITY	180L	180L
FILTERING SURFACE	11m ²	11m ²
FILTERS CLEANING	Electric	Electric
MAX HEIGHT OF UNLOADING OF CONTAINER	1430mm	1430mm
WIDTH	1800mm	1800mm
HEIGHT	1525mm	1525mm
WEIGHT WITHOUT BATTERIES	800	850

Equipped with:

- Hydraulic clearing of the container with the possibility of the total emptying out from 40 to 143cm height
- Electronic traction on two rear wheels **only model E88**
- Hydraulic traction on front wheel **only models E88 DK**
- Standard right brush and optional left brush (both with steel protection and retractable in case of knocks)
- Double suction fan
- Supper elastic large diameter wheels
- Filtrating surface from 11m² with cleaning of pocket filter by electric buzzer
- All controls are in front of the operator
- Lifting hooks
- Container capacity 180 litres
- Flashing lights / Hour counter
- Suction lock / Ergonomic commands
- Acoustic buzzer / Battery level indicator

Optional:

- Overhead protection
- Catalytic silencer **model E88 DK**
- Left side brush
- Complete lights system



Batteries options:

- 24V 320Ah c5 - 3h running time
- 24V 400Ah c5 - 5h running time

(Recommended for surfaces from 5.000 to 7.600 m²)