



# HOT STATIC



- Ideal for use in transport, construction and food industries
- Fixed installation provides protection from the often overlooked factor of constant and unsupervised movement
- Timed Stop/Start and emergency stop button
- Timed Chemical
- Low fuel & low water sensors
- Housed strong lockable cabinet manufactured from painted mild steel (**optional:** Stainless Steel)
- Pump with special seals and the nickel plated manifold housing offering enhanced protection against chemicals
- Greater security than the mobile equivalent, made possible by fixed installation
- Internal temperature adjustment & simple external controls reduce chance of operator misuse
- 12L internal stainless steel water tank and 40L steel fuel tank
- Frost protection
- Insulated chimney and rain cap



## OPTIONAL EXTRAS

- Coin or token operation
- Remote controls
- Twin cabinet

## Standard equipment



CODE	HOT STATIC	MAX PRESSURE		FLOW RATE	POWER	RPM	WATER TEMP	WEIGHT KG	DIMENSIONS LxWxH (cm)
		BAR	PSI	LTR/H					
<b>10012</b>	<b>100.12</b>	100	1450	720	2.2kW	1.450	80/100	250	87x55x147
<b>15015</b>	<b>150.15</b>	150	2.250	900	4kW	1.450	80/100	255	87x55x147
<b>20015</b>	<b>200.15</b>	200	3.000	900	5.5kW	1.450	80/100	270	87x55x147