

# EDGE

## S70 RANGE

S70 is compact man-on board sweeper suitable to clean medium and large spaces both inside and outside. The S70 frame is made by iron and, moreover, a perimeter moulding defends the risk points. The very careful design gives to S70 solidity and unity without renouncing to comfort. Aspiration, filtrating surface and filters - these three features, are the very essence of a motor-sweeper. They have always been an essential point and S70 has a high aspiration due to the high fan's rotation speed and to the large filtrating surface; this is realised with 6 cylindrical filters which total surface is of 6 m<sup>2</sup> with an electric buzzer for a more efficient and deep cleaning. The tip-up bonnet makes easy any maintenance, minimised thanks to the easy and regular structure of S70. The refuse container has an effective capacity of 62 litres and can be easily removed thanks to a wheeled frame.



### Equipped with:

- Anti-knock right side brush
- Right side brush engaging lever (next to the operator)
- Perimetral bumpers and angular front wheels
- Comfortable control panel
- Adjustable seat
- Lift-flap pedal
- Service and parking break
- Suction lock
- Filters electric buzzer
- Refuse container capacity 62 litres
- Flashing light
- Hour counter
- Horn
- Superplastic rubber wheels
- Liftings hooks
- Centrifuge clutch for cold engine starting (**model S70 / SD70**)
- Battery level indicator (**model SE70**)

### Optional:

- Reverse acoustic buzzer 100dB
- Overhead protection
- Polyester filters
- Left side brush
- Electric Assisted Discharge Device of dust container DSA - a new assisted discharge device of the dust container until 1.100 mm higher and with the possibility to unload the content in a plastic bag (can be ordered with machine only)



	SE70	S70	SD70
CODE	<b>5128</b>	<b>5129</b>	<b>5130</b>
MAIN BRUSH WIDTH Ø 285	700mm	700mm	700mm
MAIN BRUSH WIDTH + 1 BRUSH RH	920mm	920mm	920mm
MAIN BRUSH WIDTH + 2 BRUSH RH & LH	1150mm	1150mm	1150mm
MAX FORWARD SPEED	1.72 m/s	2.13 m/s	2.13 m/s
MAX. CLEANING CAPACITY (WITH 2 SIDE BRUSHES)	6200 mq/h	7700 mq/h	770 mq/h
MAX GRADIENTS IT CAN WORK ON	12% (20% optional)	14% (20% optional)	14% (20% optional)
TRACTION	Back wheels	Front wheels	Front wheels
TRANSMISSION	Electric	Oleodynamic	Oleodynamic
WHEELS	Standard non- marking wheels	Standard wheels	Standard wheels
CURVATURE RADIUS	1450mm	1450mm	1450mm
FILTERING SURFACE (NO 6 DUST FILTERS)	6mq	6mq	6mq
CONTAINER CAPACITY	62L	62L	62L
MAX LENGTH WITH CONTAINER	1430mm	1430mm	1430mm
MAX WIDTH	910mm	910mm	910mm
HEIGHT	1140mm	1140mm	1140mm
WEIGHT WITHOUT BATTERIES	260kg	300kg	310kg

**(Recommended for surfaces from 2.500 to 4.000 m<sup>2</sup>)**